



Enter a model # or keyword... [About Us](#) [Products](#) [Environmental Chambers](#) [Refurbished](#) [Rental/Lease](#) [Applications](#) [News](#) [Contact](#)

Category

- Meters & Data Acquisition (2649)
- Oscilloscopes, Logic Analyzers, Signal Generators (2254)
- Power Supplies (1955)
- Network & Spectrum Analyzers (734)
- RF & Microwave (951)
- Communications (556)
- Component Measurement (218)
- Environmental Chambers, Ovens (137)
- Thermal Imaging (248)
- Accessories & Connectivity (211)
- Other Instruments (1082)

Manufacturer

- Keysight
- Tektronix
- Fluke
- TestEquity
- Keithley
- Rohde & Schwarz
- Instek
- B&K Precision
- Anritsu
- Viavi
- Sorensen
- Magna-Power Electronics
- Chroma
- Exttech

Scroll for More

Express Order

QTY	ITEM #
1	<input type="text" value="Enter an Item #..."/>
<input type="text"/>	<input type="text"/>

Enter more [Add to Cart](#)

Electronic Measurement Solutions

Electronic Lab and Production Sol

[Products](#) [What's New and Promotions](#) [Chamber Selection Guide](#) [Refurbished](#) [Rental/Lease](#) [Educational Programs](#) [GSA Schedule](#) [E-Mail News](#)



Model 1027S Temperature Chamber Specifications

[<< Back to Model 1027S Product Page](#)

Temperature Range	-35°C to +175°C
Control Tolerance	±0.5°C (Short-term variations measured at the control sensor after stabilization)
Uniformity	±1.0°C (Variations throughout the chamber after stabilization)

Cool Down Transition Time (empty)*

Start Temp	End Temp				
	+23°C	0°C	-10°C	-20°C	-30°C
+150°C	9.0 min	14 min	17 min	20 min	26 min
+85°C	4.0 min	7.5 min	10 min	13 min	19 min
+23°C	---	1 min	2 min	4 min	9 min

Cool Down Transition Time (with 80 lb. aluminum load)*

Start Temp	End Temp				
	+23°C	0°C	-10°C	-20°C	-30°C
+150°C	20.0 min	28 min	33 min	38 min	46 min
+85°C	8.0 min	16 min	20 min	25 min	33 min

Heat Up Transition Time (empty)*

Start Temp	End Temp				
	+23°C	+50°C	+85°C	+125°C	+150°C
+23°C	---	1.5 min	7 min	14 min	20 min
0°C	1.5 min	3.5 min	13 min	20 min	23 min
-10°C	2.2 min	4.2 min	14 min	22 min	25 min
-35°C	5.5 min	10 min	16 min	23 min	29 min

Heat Up Transition Time (with 80 lb. aluminum load)*

Start Temp	End Temp				
	+23°C	+50°C	+85°C	+125°C	+150°C
0°C	5 min	13 min	23 min	36 min	45 min
-35°C	11 min	19 min	29 min	42 min	51 min

Rate Of Change

To calculate rate of change for a particular condition, take the difference between the Start Temp and End Temp and divide by the Transition Time.

Cool Down Example (empty): From +85°C to 0°C = 85°C / 7.5 min = 11.3°C/min.

Cool Down Example (with 80 lb. load): From +85°C to 0°C = 85°C / 16 min = 5.3°C/min.

Heat Up Example (empty): From 0°C to +85°C = 85°C / 13 min = 6.5°C/min.

Heat Up Example (with 80 lb. load): From 0°C to +85°C = 85°C / 23 min = 3.7°C/min.

*Note: Transition times are measured after a 2 hour soak at the respective start temperature with an empty chamber, as indicated on the temperature controller, 23 Measured with setpoint beyond the start and end temperatures. Does not include the effect of proportional band when approaching setpoint. Performance is reduced 50 Hz input power.

Live Load Capacity

+23°C	0°C	-10°C	-20°C	-30°C
4,000 Watts	2,800 Watts	2,300 Watts	1,800 Watts	1,250 Watts

Refrigeration and Heating System

Refrigerant	R-404A (Dupont HP-62)
Compressors	3.5 HP Copeland scroll compressor. More about Scroll Compressors >>
Condenser	Air Cooled

Heat of Rejection	30,200 BTUH (maximum rated chamber load at maximum cooling rate from high temperature soak)	
Heater Power	4,000 Watts @ 208 V input	
Air Flow	630 cfm	
Instrumentation		
Temperature Controller	256 step, 40 profile, ramp and soak programmable memory. RS-232/485 interface. More details >>	
Limit Controller	Independent high and low temperature limits. Triggers an audible alarm and shuts down the chamber. Relay contacts provide a safety power interlock for test sample.	
Chart Recorder	(Optional) Honeywell DR4300 Series. One pen, 10" circular chart. Mounts in lower front door.	
		

Input Power Requirements	
230 V ±10%, 60 Hz, 3 Phase	Max Current Draw 31 A; Recommended Service 40 A
208 V -5/+10%, 60 Hz, 3 Phase	Max Current Draw 26 A; Recommended Service 35 A
	Input may be configured for 230 V or 208 V in the field by changing jumpers. Three phase load is balanced. Call for other voltages operation. Customer power source must be hard-wired to the chamber by a qualified electrician. Power cord and plug is not included.

Physical Characteristics and Safety	
Inside Dimensions	40" W x 32" H x 36.5" D (27 cubic feet) 1016 mm W x 812.8 mm H x 927 mm D (764 liters)
Outside Dimensions	49" W x 73.25" H x 63" D (nominal) 1244 mm W x 1860 mm H x 1600 mm D Door latch adds 3" to width on right side. Circulator motor and housing adds 6" to height - may be removed for move-in.
Minimum Installed Clearance	18" from the left and right side 24" from the rear
Window Viewing Area	16" W x 13" H
Access Ports	4" Port on left and right side (two total) Supplied with foam plugs
Weight	Chamber Weight: 1,410 pounds Shipping Weight: 1,595 pounds

NOTE: Performance is typical and based on operation at 23°C (73°F) ambient and nominal input voltage. Designed for use in a normal conditioned laboratory. Operating ambient temperatures may result in decreased cooling performance. Additional ports and shelves will also affect performance. Operation above 30°C (85°F) or below ambient is not recommended. Performance is reduced by 17% with 50 Hz input power.

Due to continuous product improvements, specifications subject to change without notice.

[<< Back to Model 1027S Product Page](#)

About Us

- About TestEquity
- Vision and Values
- Calibration Lab
- Careers

Products

- New Test & Measurement Equipment
- New Lab and Production Tools & Supplies
- Environmental Chambers
- Refurbished Used Test Equipment
- Rental/Lease
- Educational Programs
- GSA Schedule
- Sell Your Used Equipment
- FAQs/How To Order

Applications

- Aerospace and Defense
- Automotive and Transportation
- Components/Devices/Semiconductors
- Contract Manufacturing
- Education
- Energy
- General Electronics
- Government
- Optical and Photonic
- RF Test
- The Internet of Things (IoT)
- Wireless

News

- Press Releases and News
- Trade Shows and Seminars
- E-Mail Newsletter

Contact

- Contact Form
- Address/Phone
- Purchasing Support
- Environmental Chamber Support