
PXle-8861

Specifications

2026-08-12



Contents

PXIe-8861 Specifications 3

PXIe-8861 Specifications

PXIe-8861 Specifications




Note Specifications are subject to change without notice.



Caution Using the PXIe-8861 controller in a manner not described in this user manual can impair the protection the controller provides.

PXIe-8861 Front Panel

Figure 1. PXIe-8861 Front Panel




1. GPIB
2. Ethernet
3. USB 2.0
4. RS-232 Serial
5. Trigger
6. Reset Button
7. USB 3.0
8. DisplayPort 1.1
9. DisplayPort 1.2
10. Thunderbolt
11. LEDs
12. Removable Hard Drive Shuttle (Removable Hard Drive Variant Only)

Front Panel Dimensions

The following figure shows the front panel layout and dimensions of the PXle-8861. Dimensions are in inches (millimeters).

Figure 2. PXle-8861 Front Panel Layout and Dimensions



Features

CPU	Intel® Xeon® Processor E3-1515M v5
Cache	8 MB SmartCache
Quad-Channel DDR4-2133 (PC-17000)	8 GB standard, 32 GB maximum
Storage	512 GB (or greater) solid-state, NVME
Video	1 DisplayPort 1.1, 1 DisplayPort 1.2
Ethernet	1 i219 port; 1 i210 port, 1588, 10/100/1000 Base T

PXI Express 4 Link Configuration	x4, x4, x4, x4
PXI Express 2 Link Configuration	x8, x8
GPIB (IEEE 488 Controller)	1 micro-GPIB
Serial Port (RS-232)	1 DB-9
Thunderbolt 3 Ports	2 Type-C
Hi-Speed USB (2.0) Ports	4 Type-A
SuperSpeed USB (3.0) Ports	2 Type-A
PXI Trigger Bus Input/Output	1 SMB
Installed Operating System	Windows 10 IoT Enterprise or NI Linux Real-Time
Trusted Platform Module	Optional TPM 2.0 (Infineon/ST TPM for global market, no TPM available for China market)

Electrical Characteristics



Note Does not include any attached devices.

Voltage (V)	Current (Amps) Typical	Current (Amps) Maximum
+3.3 V	3.75 A	4.25 A
+5 V	2.0 A	2.5 A
+12 V	6.0 A	7.6 A
-12 V	0 A	0 A
+5 V _{Aux}	0.75 A	0.8 A



Note Power delivered to external loads through USB or Thunderbolt 3 ports should be included in system power budgets that include this controller module and peripheral modules.

Physical

Board dimensions	Four-wide 3U PXI Express module
Slot requirements	One system slot plus three controller expansion slots
Compatibility	Fully compatible with <i>PXI Express Specification 1.0</i>
Weight	1.2 kg (2.6 lb) typical

Environment

Maximum altitude	4,600 m (570 mbar) (at 25 °C ambient)
Pollution Degree	2

Indoor use only.

Operating Environment



Caution The operating temperature must not be exceeded, even when used in a chassis with a higher temperature range.

Ambient temperature range	0 °C to 55 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2. Meets MIL-PRF-28800F Class 3 low temperature limit and MIL-PRF-28800F Class 2 high temperature limit.)
---------------------------	--

Relative humidity range	10% to 90%, noncondensing (Tested in accordance with IEC-60068-2-56.)
-------------------------	---

Storage Environment

Ambient temperature range ¹	-40 °C to 71 °C (Tested in accordance with IEC 60068-2-1 and IEC 60068-2-2. Meets MIL-PRF-28800F Class 3 limits.)
Relative humidity range	5% to 95%, noncondensing (Tested in accordance with IEC 60068-2-56.)

Shock and Vibration

Operating shock	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC 60068-2-27. Meets MIL-PRF-28800F Class 2 limits.)
Random vibration	
Operating	5 Hz to 500 Hz, 0.3 g _{rms} (with solid-state hard drive)
Nonoperating ¹	5 Hz to 500 Hz, 2.4 g _{rms} (Tested in accordance with IEC 60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)

Safety

This product is designed to meet the requirements of the following standards of safety for information technology equipment:

1. CPU performance may decrease for some workloads if a unit is stored at the extreme ambient temperature range and then subjected to max nonoperating random vibration limits.

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



Note For UL and other safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia and New Zealand (per CISPR 11) Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations and certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory

compliance information. To obtain product certifications and the DoC for NI products, visit ni.com/product-certifications, search by model number, and click the appropriate link.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Engineering a Healthy Planet* web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

Battery Replacement and Disposal

-  **Battery Directive**—This product contains a long-life coin cell battery. If you need to replace it, use the Return Material Authorization (RMA) process or contact an authorized NI service representative. For more information about compliance with the EU Battery Directive 2023/1542 about Batteries and Accumulators and Waste Batteries and Accumulators, visit ni.com/environment/batterydirective.

电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)