

POLARIZATION SCRAMBLER

IQS-5100B

R&D AND MANUFACTURING—OPTICAL



- Very low activation dependent loss
- High-performance technical specifications
- Wide spectral range of 1260 nm to 1650 nm

Production line testing requires a fast, reliable instrument with low activation dependent loss, coupled with a wide wavelength range. The dependability of the IQS-5100B comes from its unique fiber-based design, which features no mechanical parts.

The IQS-5100B's activation loss is much lower than other polarization scramblers, resulting in very small power variations at the scrambler output. Accurate polarization measurements are dependent on low activation loss since it is impossible to compensate for power variations at the scrambler output. The IQS-5100B's low ADL helps you to achieve fast, simple polarization dependent measurements.

Applications

- Polarization-dependent loss (PDL) measurements on passive components
- Polarization-dependent gain (PDG) measurements on EDFAs
- Polarization-dependent responsivity (PDR) measurements for detectors and receivers

Many types of polarization tests require varying the polarization states to cover most of the Poincaré sphere. Perform fast and random changes of the polarization state of a signal with the IQS-5100B Polarization Scrambler.

Combine the IQS-5100B Polarization Scrambler with the IQS-1700 High Performance Power Meter and the IQS-2600B Tunable Laser Source or the IQS-2400 WDM Laser Source for a fast, complete PDL testing system.

THE IQS-500 INTELLIGENT TEST SYSTEM

The new IQS-500 Intelligent Test System provides a flexible approach to optical test and measurement for manufacturing, automation, optical qualification and R&D. It combines powerful features and control capabilities for up to 100 modules.

Based on standard industrial PC architecture, the IQS-500 Intelligent Test System is a scalable modular platform that includes controllers, expansion units and a comprehensive range of plug-in test modules. The IQS-500 is also backward-compatible with most modules from EXFO's IQ generation, allowing you to maximize the return on previous investments. The IQS-500 Intelligent Test System offers a powerful, easy-to-use environment to match your most demanding needs.

SPECIFICATIONS ^a

Wavelength range (nm)	1260 to 1650	
Activation dependent loss (dB)	0.006 (typ.)	0.01 (max.)
Extinction ratio (dB)	> 40	
Insertion loss (dB)	< 0.1	(excluding connectors)
	≤ 1	(with connectors)
Return loss (dB)	≥ 50 (UPC Connector)	
Scrambling (s)	1 to 99.9 s	
Poincaré sphere coverage	1 scrambling period: 98 %	2 scrambling periods: 99 %

GENERAL SPECIFICATIONS

Temperature	operating	0 °C to 40 °C	(32 °F to 104 °F)
	storage	-20 °C to 70 °C	(-4 °F to 158 °F)
Dimensions (H x W x D)	125 mm x 36 mm x 282 mm		(4 15/16 in x 1 7/16 in x 11 1/8 in)
Weight	0.84 kg		(1.85 lb)

ORDERING INFORMATION

IQS-5100B-01-B-XX

Output connector ^{b, c}

EI-EUI-28 = UPC/DIN 47256
EI-EUI-89 = UPC/FC narrow key
EI-EUI-91 = UPC/SC
EI-EUI-95 = UPC/E-2000

Example: IQS-5100B-01-B-EI-EUI-89

NOTES

- At 23 °C and 1550 nm. Insertion loss changes with connector type.
- Input connector APC Universal Interface only.
- Output connector UPC Universal Interface only.

Find out more about EXFO's extensive line of high-performance portable instruments by visiting our website at www.EXFO.com.

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: 1 418 683-0211 | Fax: 1 418 683-2170 | info@EXFO.com

Toll-free: 1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3701 Plano Parkway, Suite 160	Plano, TX 75075 USA	Tel.: 1 800 663-3936	Fax: 1 972 836-0164
EXFO Europe	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 2380 246810	Fax: +44 2380 246801
EXFO Asia	151 Chin Swee Road, #03-29 Manhattan House	SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	No.88 Fuhua, First Road	Shenzhen 518048, CHINA	Tel.: +86 (755) 8203 2300	Fax: +86 (755) 8203 2306
	Central Tower, Room 801, Futian District			
	Beijing New Century Hotel Office Tower, Room 1754-1755	Beijing 100044 P. R. CHINA	Tel.: +86 (10) 6849 2738	Fax: +86 (10) 6849 2662
	No. 6 Southern Capital Gym Road			

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. All of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor. For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.