
General specifications

Use	Indoor
Temperature	Operating 15°C to +35°C (59°F to +95°F) Non-operating -40°C to +70°C (-40°F to +158°F)

Humidity

NOTE

This test requires a one hour warm-up period.

Operating up to 95% humidity (non-condensing) at +35 °C (+95 °F)
Non-operating up to 90% relative humidity at +65 °C (+149 °F)

Altitude	Operating up to 4,600 meters (15,000 ft) Non-operating up to 15,300 meters (50,000 ft)
-----------------	---

Vibration	Operating Random vibration 5–500 Hz, 10 minutes per axis, 0.3 g_{rms} Non-operating Random vibration 5–500 Hz, 10 minutes per axis, 2.41 g_{rms} ; Resonant search, 5 to 500 Hz swept sine, 1 octave/minute sweep rate, 0.75g, 5 minute resonant dwell at 4 resonances per axis.
------------------	---

Specifications and Characteristics

Power Requirements	Voltage	90 to 132 or 198 to 264 Vac, 48-66 Hz
	Power	1200 VA; 650 W
Weight (approximate)	Net	24.5 kg (54 lb)
	Shipping	31.8 kg (70 lb)
Dimensions	H × W × D	238.2 mm × 433.6 mm × 637.38 mm (9.378 in × 17.071 in × 25.094 in)